



- Alternating current (AC) MMA electrode welding machine, 160A. Supplied with accessories for welding.
- Usable electrodes: rutile up to 4 mm.
- Continuous adjustment of welding current.
- Thermostatic protection.

TECHNICAL DATA

CODE	814104	MAX NO LOAD VOLTAGE IN AC	49 V	INSULATION CLASS	H
SINGLEPHASE MAINS VOLTAGE	230 V	ABSORBED POWER	2,5 kW	PROTECTION DEGREE	IP21
MAINS FREQUENCY	50 / 60 Hz	MAINS FUSE	16 A	DIMENSIONS (LxWxH)	37 x 25 x 31 cm
CURRENT CONTROL RANGE AC	50 - 160 A	D.USABLE ELECTRODES AC	2 - 4 mm	WEIGHT	15,7 kg

SUPPLIED ACCESSORIES

124502	CABLE 16 MMQ 1,8 M
712001	COLORADO 150B WORK CLAMP 150A
712139	SLAG REMOVER
712250	MASK
712257	FILTER 51X108
712260	DALLAS 300 ELECTRODE HOLDER 300A

DESCRIPTION

MMA stick electrode welding machine in alternating current (AC).
 Stepless regulation of welding current.
 With thermostatic protection.
 Use with electrodes: rutile.
 Complete with MMA welding accessories.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE